

Key Features

- Purpose-built to scale VXLAN or OpenFlow* based Spine or Leaf data center topologies leveraging high-performance TCAM
- First system to partition and optimize the number of TCAM entries required for flow rules
- First open switch for open networks leveraging hardware-agnostic operating system
- Fully non-blocking 40 GbE fabric with ultra-low latency



Pica8 P-5401

- 32 x 40 GbE QSFP+ port base unit
- Cost-effective 40 GbE aggregation

Overview

Pica8's purpose-built open switches are ideal for cloud data centers that require flexibility and adaptability. Pica8™ open switches seamlessly integrate with today's data center applications on traditional network architectures, while allowing the exploration of new software defined networking (SDN) technologies, such as OpenFlow.

Pica8 white box switches run PicOS™, an open network operating system (OS) that runs standards-based Layer 2 / Layer 3 protocols with industry-leading OpenFlow 1.4 / Open-vSwitch (OVS) 2.0 integration. OVS runs as a process within PicOS, and provides the OpenFlow interface for external programmability. PicOS utilizes proven high-performance hardware to deliver wire speed through a switching fabric capacity of 2.56 Tbps.

Leverage Pica8's operating system - PicOS - for two powerful modes of operation

| | Layer 2 / Layer 3 Mode | Open vSwitch (OVS) Mode |
|-----------------|--|---|
| OPEN | <ul style="list-style-type: none"> • Switching platform with Debian Linux on board and accessible • Programmable and customize by leveraging vast high-quality Linux tools | <ul style="list-style-type: none"> • Industry-leading OpenFlow 1.4 support through Open vSwitch (OVS) 2.0 integration • Leverage production-ready OVS switches for your CloudStack / OpenStack projects |
| FLEXIBLE | <ul style="list-style-type: none"> • High-performance Layer 2 / Layer 3 switching platform for both IPv4 and IPv6 networks, seamlessly integrating into existing architectures • Tune the fabric to meet your application needs, selectable store-and-forward or cut-through switching modes for ultra-low latency | <ul style="list-style-type: none"> • Interoperable with multiple Open Source OpenFlow controllers such as Ryu, Floodlight, NOX, and Trema • Leverage different controllers and reference architectures |
| ADAPTIVE | <ul style="list-style-type: none"> • PicOS a multiprocess OS, ensures each process has independent memory space, thread control, and interrupt handling for improved feature scaling | <ul style="list-style-type: none"> • Seamlessly add new protocols to PicOS, a multiprocess OS • Investment protection as your application needs change |

* Only OpenFlow features supported in hardware are supported, to ensure optimum performance

PRODUCT REFERENCE GUIDE



| P-5401 | |
|--|--|
| Performance | |
| Switch Fabric Capacity (Tbps) | 2.56 |
| Forwarding Capacity (Mpps) | 1501 (Based on 12 Bytes interpacket gap condition) |
| Forwarding Options | Store-and-Forward / Cut-Through |
| Packet Buffer Memory (MB) | 12 |
| Latency (ns) | 617ns / 642ns (64 / 1,518 Byte Frames) |
| System Memory (GB) | 4 |
| SD/CF Memory (GB) | 8 |
| CPU | P2020 / Trident2 |
| Ports | |
| 32-Port Base Unit | 40 GbE QSFP+ |
| Uplink Options | NA |
| SFP+ / QSFP+ Options | SR4, LR4, CR4 |
| Console Port | 1 x RJ45 Serial |
| Management Port | 1 x 10/100/1000BASE-T |
| Layer 2 / Layer 3 Features | |
| ACL Entries | 4K |
| Maximum MAC Addresses | 288K |
| Maximum VLANs | 4,094 |
| Link Aggregation (Groups/Ports) | 1024 / 8 |
| Jumbo Frames (Bytes) | 12,000 |
| Maximum Routes | 112K IPv4, 56K IPv6 |
| Spanning Tree | STP/RSTP/MSTP |
| IPv4 Routing | RIP, OSPFv2/ECMP, BGP-4/ECMP, Static |
| IPv6 Routing | RIPng, OSPFv3, Static |
| Multicast Routing | PIM-SM, IGMP, IGMP Snooping |
| OpenFlow Support | |
| Large TCAM | Yes |
| Open vSwitch | v2.0 |
| MPLS over OVS | Yes |
| GRE Tunneling | Yes |
| Physical & Environmental Specifications | |
| Size (Inches) | 1.73 (H) x 17.3 (L) x 16.0 (D) |
| Weight (lbs) | 17.63 |
| MTBF (Hours) | 187,444 |
| Air Flow | Front to Back / Back to Front |
| Hot-Swappable Redundant Power | Yes |
| Power Draw (Watts) | 460 |
| Input Voltage / Frequency | 100 - 240 VAC / 50 - 60 Hz |
| Operating Temperature | 32 - 113 °F (0 - 45 °C) |
| Operating Humidity | 95% Maximum Relative Humidity |
| LEDs | Port Status (Green), Activity Status (Blinking) |
| Regulatory Compliance | |
| Emissions | FCC, CE, VCCI, CCC, BSMI |
| Safety | UL, CE |
| RoHS | Yes |

Pica8, Inc. Corporate Headquarters

1032 Elwell Court, Suite 105
Palo Alto, California 94303, USA
650-614-5838 | www.pica8.com
© Pica8, Inc., 2014. All rights reserved.
Produced in the United States 07/14.

Pica8 and PicOS are trademarks of Pica8, Inc.

Pica8 and PicOS trademarks are intended and authorized for use only in countries and jurisdictions in which Pica8, Inc. has obtained the rights to use, market and advertise the brand. Pica8, Inc. shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Pica8, Inc. products or services do not imply that Pica8, Inc. intends to make these available in all countries in which it operates. Contact Pica8, Inc. for additional information.